



FOLIANT EU, s.r.o.  
Stefanikova 1347/III  
293 01 Mlada Boleslav  
Czech Republic  
tel +420 326 370 711  
[foliant@foliant.eu](mailto:foliant@foliant.eu) | [www.foliant.eu](http://www.foliant.eu)

# FOLIANT TAURUS 760 SF

The FOLIANT Taurus 760 SF is a very compact and fast industrial laminating machine, constructed for a heavy duty with an integrated suction feeder and a high speed bump separator and with an optional pallet stacker. **The machine maximum speed is up to 30 m/min.**, while maximum performance is 1700 sheets per hour of B1 portrait or 3400 sheets per hour of B2 landscape (white paper 200 gsm).



## FEEDER

The FOLIANT Taurus 760 SF is equipped with a rising pile back separation stream feeder, with a suction feed head. It is driven by an Omron servo motor and controlled by a machine central PLC. The Becker vacuum pump is used for sheets back and sides airing. The overlaps are electronically controlled, in an „in-run“ automatic mode, from the touch screen. The accuracy is +/- 2 mm under-lap (in a constant speed). The feeder is fitted with a lifting plate and its capacity is a 45 cm pile of paper.

## LAMINATOR

The FOLIANT Taurus 760 SF laminator maximum sheet size is 76 x 110 cm. The minimum sheet size is 30 x 25 cm (A4). The FOLIANT Taurus 760 SF machine is a single sided thermal industrial laminator laminating the paper 115 – 500 gsm, with an unique „U“ cross bar for the thin sheets flat and safety high pressure lamination, mounted in the front of the main laminating rollers, with an „In run“ adjustable de-curl bar.

The roll of a film is mounted on an air shaft that allows very convenient, easy and precise film positioning. The shaft capacity is up to 3000 m of the 24 - 31 microns film. The film holder unit is equipped with a trim slit and a perforating wheel.

The laminating process is done between two laminating rollers - a highly polished chrome roller, and a lower hard rubber pressure roller. The laminating roller is heated with a dry electric system inside the roller, with a sensitive in-roll temperature sensor. The warming up time is shorter than 10 minutes. The pressure is pneumatically adjustable, with an extra independent control knob for each roller edge.

The machine is fitted with OMRON Programmable Logic Controllers, which controls all machines' functions. Used PLC system includes many automation items for a machine easy control and a reliable lamination. The whole machine is controlled by an interactive easy understandable icon touch screen panel – no language version is needed.

## SEPARATOR

The integrated bump separator (sheeter) is equipped with a pair of fast cycling rollers. The process is controlled from the machine PLC unit. The separated sheets are delivered into a vibrating jogger (optional) or a pallet stacker (optional).

## LAMINATING FILMS

The machine laminates the BOPP films (23 – 42 microns) and Nylon films (max. 35 microns). The PET films (max. 35 microns) can be laminated with the optional module only.

## OPTIONS

### JOGGER 760 (OPTIONAL)\*

It is an adjustable vibrating reception unit for the laminated sheets stocking. Its capacity is limited up to a 10 cm pile of sheets.

### PALLET STACKER (OPTIONAL)\*

It is a device equipped with a pallet trolley, pneumatically controlled from the machine PLC, which loads the laminated sheets into a high pile. Its capacity is 65 cm pile of sheets. It is based on a manual scissors lift table (hydraulic) and sensors for its pneumatic control. The pallet can be manipulated either from the operator's side (it saves the manipulation space) or from behind.

### PET FILMS LAMINATION MODULE (OPTIONAL)

It is a module integrated inside the separator for the PET films (max. 35 microns) processing.

### FILM LOADER/MANIPULATOR (OPTIONAL)

It is an electric lift with a film core adaptor for loading heavy rolls of film (max. capacity 125 kg). The device is not integrated with the machine. It is only connected with the machine's electric circuits.

\*Important – the machine must be operated either with a Pallet Stacker or with a Jogger.



Optional Jogger



Optional Pallet Stacker



Optional Film loader

Foliant Taurus 760 SF

<b>Max Speed</b>	30 m / min	<b>Film Micro Adjustable Air Shaft</b>	Standard
<b>Feeding</b>	Automatic	<b>Warming up Time</b>	8 min
<b>Feeding System</b>	Suction Feeding Head	<b>Temperature Control</b>	80 - 140°C
<b>Feeder's Load Capacity</b>	45 cm	<b>Power Supply</b>	3 ph., 400 V AC, 50-60 Hz
<b>Overlaps</b>	Automatic, PLC Control	<b>Power</b>	8500 W
<b>Overlaps Accuracy</b>	+ / - 2 mm	<b>Floor space (w x l)</b>	138 x 295 cm
<b>Separation</b>	Automatic, Bump Rollers	<b>Weight</b>	710 kg
<b>Paper Weight</b>	115 - 500 gsm	<b>Module for PET Films Processing</b>	Optional
<b>Main Rollers Pressure</b>	Pneumatic	<b>Jogger 760</b>	Optional
<b>External Compressor</b>	150 l / min, 6 - 8 bar	<b>Pallet Stacker</b>	Optional
<b>Min. Sheets Size (w x l)</b>	30 x 25 cm	<b>Pallet Stacker Capacity</b>	65 cm
<b>Max. Sheets (w x l)</b>	76 x 110 cm	<b>Film Loader (Electric)</b>	Optional
<b>Max. Performance</b>	1700 B1 / hour		